

MI MICHIGAN COLLECTION

Michigan Collection
 [Smooth | Solid | 3/4"]

#259 SM-S, #260 SM-S, #261 SM-S, #263 SM-S, #264 SM-S

SERIES INFORMATION:

Colors:	Species/Janka	Thickness	Width	Length	Wear Layer	SF/BOX	BX/PLT	SF/PLT	BX/WGT	SF/WGT	Waste %
#259 SM-S-#264 SM-S	Hickory (1780)	3/4"	4 1/4"	1'-5'	3/16"	19.53	48	937	61	3.13 lbs.	5-7%

INSTALLATION

- ☒ Nail
- ☒ Nail/Glue Assist (Preferred)
- ☒ Glue Only (with limitations)
- ☐ Float
- ☐ Click
- ☐ Below Grade
- ☐ Radiant Heat

ADDITIONAL INFORMATION:

Core Construction	Solid Wood
Joint System	Tongue and Groove
Edge Profile	Micro Beveled
Texture	Smooth
Finish Type	9 Finish Coats - UV cured urethane infused with aluminum oxide
Gloss Levels	19% -21%
Maintenance	Bona Hardwood Formula
Repair Finish	Can be screened and recoated with Bona HD Traffic (or similar)
Expansion Requirements	Requires 1/2" expansion gap
Fastener Requirements	15-16 gauge, L/T cleats, or 7/16" to 1/2" crown staples, minimum 1 3/4" Length. Fastener spacing 1 1/2" from the board ends and every 6" - 8" along the tongue.
Uses	Residential Light Duty Commercial

COMPLIANCE:

This series has been tested and contains the following certifications:



LIMITED WARRANTY

Finish: 25 year
 Structural: Lifetime



COMMON QUESTIONS:

SUBSTRATE REQUIREMENTS

Structurally sound, well bounded, flat to within 3/16" in 10' radius, or 1/8" in 6' radius. Vertical deflection cannot exceed 1/4" in 10' radius, or more than 1/16" between the floor joist.

APPROVED SUBSTRATES

Underlayment APA grade CDX plywood/OSB. See NWFA guidelines for 3000 PSI concrete or 2500 PSI gypcrete.

WOOD SUBFLOOR (EMC) MOISTURE CONTENT REQUIREMENTS

Solid wood MC (moisture content) must test within 2% of the wood subfloor. Neither can exceed 12%.

CONCRETE AND GYPCRETE MOISTURE EMISSIONS, RH, AND PH REQUIREMENTS

Random width and/or narrower than 4 1/4" ONLY. Check with NWFA for an approved adhesive and/or moisture mitigation system for concrete/gypcrete, RH, pH, and installation requirements. (Bond and moisture mitigation warranties comes solely from glue and/or vapor barrier manufacturer.)

JOB SITE CONDITION RANGES

Prior, during, and after installation, the jobsite RH must be maintained between 35-55%, and the room temperature between 60-80°F.

ACCLIMATION TIME FRAME

Minimum 72 hours to reach room temperature between 60-80 °F. The subfloor and the wood flooring MC (moisture content) must test within 2% of each other and does exceed 12%. If the MC falls outside this range, a longer acclimation period is required to reach equilibrium.

CAN WE INSTALL A CUSHION UNDERNEATH THE FLOOR?

Cushion is not compatible.

RUG COMPATIBILITY

Must be breathable, non abrasive, natural fiber rugs. Please see RugPadUSA.com. For example; Eco Plush 3/8", Contour Lock, RugPro, or Superior Lock 1/4".



Note: For accuracy, we used actual material to create these product images. Please be aware that colors on printed media or displayed on a screen may vary from the actual product.

MI MICHIGAN COLLECTION

Michigan Collection
[Smooth | Solid | 3/4"]



SMOOTH



Color # 259 SM-S Hickory

Color # 263 SM-S Hickory

Color # 260 SM-S Hickory

Color # 264 SM-S Hickory

Color # 261 SM-S Hickory