

MM MARKET & MAIN COLLECTION

Market & Main Collection

[Hand Scraped, Registered Embossed | WPC | 7.5MM]

#1350 HS-TUF, #1351 HS-TUF, #1352 HS-TUF, #1353 HS-TUF,
 #1354 HS-TUF, #1360 RE-TUF, #1361 RE-TUF, #1362 RE-TUF,
 #1363 RE-TUF, #1364 RE-TUF, #1365 RE-TUF, #1366 RE-TUF

SERIES INFORMATION:

Colors:	Thickness	Width	Repeat Pattern	Length	Wear Layer	SF/BOX	BX/PLT	SF/PLT	BX/WGT	SF/WGT	Waste %
#1350-#1354, #1365-#1366	7.5MM	7 1/8"	5+	60"	20MIL	17.35	75	1301	30	1.73 lbs	5-8%
#1360-#1364	7.5MM	7 7/8"	5+	60"	20MIL	19.56	75	1467	32	1.64 lbs	5-8%

INSTALLATION

- ☒ Nail
- ☒ Float
- ☒ Radiant Heat
- ☒ Nail/Glue Assist
- ☒ Click
- ☒ Glue Only
- ☒ Below Grade

ADDITIONAL INFORMATION:

Core Construction	Tuffcore WPC (Polyvinyl Chloride)
Core Type	PVC (Virgin) 970+ PSI
Joint System	Valinge 2g Click - Angle / Angle
Texture	Reg. Embossed or Hand Scraped (Depending on color)
Edge Profile	Enhanced Bevel 1mm
Finish Type	2 Coats of UV cured urethane with hardener
Gloss Levels	5 - 7%
Maintenance	ZEP Neutral Floor Cleaner
Repair Finish	Dr. Schutz Scratch Fix - Vinyl Design Floor Repair
Expansion Requirements	1/4" expansion gap for the first 20 Lineal feet (length or width). Add additional 1/16" for every 5' of install (length or width) upto 5/8". T-molds are required for rooms exceeding 40 lineal feet in length and width and 35 lineal feet for installations over in floor radiant heat.
Uses	Residential - Commercial

COMPLIANCE:

This series has been tested and contains the following certifications:



877.238.3225 | www.my-nfp.com



HAND SCRAPED



REG. EMBOSS

LIMITED WARRANTY

Finish: Limited Lifetime

Structural: 10 year Commercial



WATERPROOF

Invulnerable To Water

COMMON QUESTIONS:

SUBSTRATE REQUIREMENTS

Structurally sound, well bounded, flat to within 3/16" in 10' radius or 1/8" in 6' radius, vertical deflection cannot exceed 1/4" in 10' Radius, or more than 1/16" between the floor joist.

APPROVED SUBSTRATES

Underlayment APA grade CDX plywood/OSB, 3000 PSI concrete or 2500 PSI gypcrete. Underlayment grade MDF. See installation guide for additional approved substrates.

WOOD SUBFLOOR (EMC) MOISTURE CONTENT REQUIREMENTS

Should not exceed 12% MC (moisture content).

CONCRETE AND GYPCRETE MOISTURE EMISSIONS, RH, AND PH REQUIREMENTS

Properly install a minimum of 6mil plastic over the entire substrate. Overlap all seams 12" and tape all seams with moisture proof tape.

JOBSITE CONDITION RANGES

RH between 30-60% and room temperature between 60 to 80°F. Post installation temperature range must be within 60 to 142°F.

ACCLIMATION TIMEFRAME

No acclimation is required if the product was stored and/or transported in 60 to 80°F for at least 24 hours prior to installation. Otherwise, it must acclimate for a minimum of 24 hours. Please see installation guide for radiant heat application.

CAN WE INSTALL A CUSHION UNDERNEATH THE FLOOR?

This product has an attached 1mm thick high density cork underlayment. An additional cushion is not needed. However, only the NFP #60PVC high density cushion can be installed underneath.

RUG COMPATIBILITY

Must be breathable, non abrasive, natural fiber rugs. Please see RugPadUSA.com. For example; Anchor Grip, Nature's Grip, RugPro, or Super Lock Natural.



Note: For accuracy, we used actual material to create these product images. Please be aware that colors on printed media or displayed on a screen may vary from the actual product.

MM MARKET & MAIN COLLECTION

Market & Main Collection

[Hand Scraped, Registered Embossed | WPC | 7.5MM]



Color # 1350 HS-TUF Acacia

Color # 1351 HS-TUF Hickory

Color # 1352 HS-TUF Oak

Color # 1353 HS-TUF Oak

Color # 1354 HS-TUF Hickory

Color # 1360 RE-TUF Oak

Color # 1361 RE-TUF Oak

Color # 1362 RE-TUF Oak

Color # 1363 RE-TUF Oak

Color # 1364 RE-TUF Oak

Color # 1365 RE-TUF Oak